


This ULTRA-COMPACT single circuit product is targeting mini-chiller and reversible Air-To-Water heat pumps. Large ports and innovative plate design enables an effective operating range up to 18 kW QD20 is delivering 30% less water pressure drop compared to similar products on the market SWEP's versatile H pressure products enable efficient heat exchange in applications requiring high pressures. It is optimized for high performance with the refrigerant R410A & R32.


Connections*



*For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.

Pressure classes


M Medium, evaluated per EN 13345.



Max number of plates (NoP)	82
Port size F1/P1	25 mm (0.984 in)
Port size F2/P2	25 mm (0.984 in)
Port size F3/P3	16 mm (0.630 in)
Port size F4/P4	25 mm (0.984 in)
Max volume flow	9.7 m ³ /h (42.7 gpm)
Channel volume (SI)	0.031 / 0.03 dm ³
Channel volume (US)	0.00111 / 0.00106 ft ³

Materials	Channel plate	Brazing
NSC	Stainless steel	Copper

Size	Height of plate pack	Total weight
	6+(1,46×NoP) mm	1,04+(0,071×NoP) kg
	0.236+(0.057×NoP) in	2.30+(0.156×NoP) lb



Third party approvals


SWEP BPHEs are generally approved by listed below certification organizations:

- Europe, Pressure Equipment Directive (PED)**
- America, Underwriters Laboratories Inc (UL)**
- Japan, Kouatsu-Gas Hoan Kyoukai (KHK)**

Additionally SWEP holds approvals from a vast variety of other certification organizations. For approval information regarding a specific product please contact your local SWEP representative. SWEP reserves the right to make changes without prior notice.

The BPHE concept

The Brazed Plate Heat Exchanger (BPHE) is constructed as a plate package of corrugated channel plates with a filler material between each plate. During the vacuum brazing process, the filler material forms a brazed joint at every contact point between the plates, creating complex channels. The BPHE allows media at different temperatures to come into close proximity, separated only by channel plates that enable heat from one media to be transferred to the other with very high efficiency. The concept is similar to other plate and frame technology, but without the gaskets and frame parts.



SSP calculation software

With SWEP's unique SSP, the SWEP Software Package, you can do advanced heat transfer calculations yourself, and choose the product solution that suits your application best. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, or you would like to discuss different product solutions, SWEP offers all the service and support your need.

Material disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still subject to corrosion if used in unsuitable environments.